

SERIE 6 PUR M1

质量轻，弯曲非常灵活，材质
PU包覆涤纶布、钢丝



Structure : Light weight flexible ducting made out of polyurethane-coated polyester fabric fire-resistant according to M1 norm, reinforced with spring steel wire for grounding. Halogen and softener free.

Applications : Designed for suction of very hot air, dust, oil and petrol fumes. Excellent flexibility, good abrasion resistance, to be use where fire resistance is required.

结构：质量轻，弯曲灵活，PU包覆涤纶布材质，防火等级M1，螺旋钢丝加强，不含卤素和软化剂

应用：：热风输送，物料干燥，化工行业，进气管。弯曲非常灵活，耐磨性能好，有耐火需求的环境下使用。



int mm	kg/m	mm	mm	bar	bar	m
60	0,220	0,40	45	0,80	0,16	10
70	0,260	0,40	50	0,70	0,14	10
75	0,280	0,40	55	0,60	0,10	10
80	0,300	0,40	55	0,80	0,10	10
90	0,330	0,40	65	0,60	0,08	10
100	0,350	0,40	70	0,60	0,08	10
110	0,380	0,40	75	0,50	0,07	10
120	0,420	0,40	85	0,50	0,07	10
125	0,440	0,40	85	0,50	0,07	10
130	0,450	0,40	90	0,40	0,06	10
140	0,480	0,40	100	0,40	0,06	10
150	0,530	0,40	105	0,30	0,06	10
160	0,560	0,40	110	0,25	0,05	10
170	0,600	0,40	120	0,25	0,05	10
180	0,630	0,40	130	0,20	0,04	10
200	0,790	0,40	140	0,20	0,04	10
204	0,800	0,40	140	0,15	0,03	10
225	0,890	0,40	160	0,15	0,03	10
250	0,990	0,40	175	0,15	0,03	10
275	1,100	0,40	190	0,10	0,02	10
280	1,120	0,40	200	0,10	0,02	10
300	1,200	0,40	210	0,10	0,02	10
304	1,220	0,40	210	0,10	0,02	10
315	1,630	0,40	220	0,06	0,02	10
325	1,680	0,40	230	0,06	0,02	10
350	1,800	0,40	250	0,06	0,02	10
400	2,100	0,40	280	0,04	0,01	5
450	2,350	0,40	315	0,04	0,01	5
500	2,600	0,40	350	0,03	0,01	5

温度范围：

- 40 / + 180 °C
- 40 / + 356 °F

特性：

PU包覆涤纶布材质，耐火等级M1，耐高温，耐油耐汽油，内壁光滑，弯曲灵活

颜色：绿色：

